

PL-CN50-COB -2000-927-60D-G3

PL COIN 50 COB G3 | Spot-, Down- and Wallmount Light Engines and Modules



Product family features

- Color consistency < 2 SDCM (15D version <3 SDCM)
- TM30 compliant
- High flux output up to 1500 lm
- Beam angle: 15°, 24°, 40°, 60°
- Type of protection: IP20

Product family benefits

- Compatible with conventional MR16 lamps
- Precise optical control and free from multi-shadow issue
- Replaceable front cover to maximize optics flexibility and future extension

Areas of application

- Retail, shop, restaurant, hospitality
- High-end residential
- Suitable for indoor applications
- Connecting multiple modules in parallel on one LED driver is not permitted
- Connecting multiple modules in series on one LED driver is not recommended
- Do not use in sealed fixtures
- Avoid covering the lens with dust or any object

Technical data

Electrical data

Nominal current	0.5 A
Type of current	DC
On-mode power	17.2 W
Energy consumption in on-mode	17.2 kWh/1000h
Maximum forward voltage	36 V

Photometrical data

Luminous efficacy	102.5 lm/W
Peak luminous intensity	1990
Correlated color temperature CCT	2700 K
Colour consistency (McAdam ellipses)	2
Useful luminous flux (Φ_{use})	1573 lm
Color rendering index Ra	90

Light technical data

Beam angle	60 °
Starting time	0 s
Warm-up time (60 %)	0 s

LED module information

Number of LEDs per module	1
---------------------------	---

Dimensions & weight

Product weight	121.00 g
Height EPREL	75 mm
Length EPREL	50 mm
Width EPREL	50 mm

Temperatures & operating conditions

Performance temp. acc. to IEC 62717	70 °C
Maximum temperature at tc test point	95 °C

Lifespan

Number of switching cycles	>15000
Lumen maintenance factor LMF	96
L70B50 lifetime	50000 h

Additional product data

Lighting technology used	LED
--------------------------	-----

Capabilities

Dimmable	Yes
----------	-----

Certificates & standards

Standards	IEC 62778 / IEC 60598-1 / EN 62031 / EN 55015 / EN 61547 / IEC 61000-3-2 / IEC 61000-3-3
Type of protection	IP20
Energy efficiency class	F

Logistical data

Commodity code	85395100000
Applicable region	APAC (excl. China, India, Japan) / CHINA / INDIA / JAPAN / EUROPE / MEA / SOUTH AMERICA

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-08-2026
Primary Article Identifier	6937186151599
Declaration No. in SCIP database	In work
SCIP_ID	

Download Data

File		
IES data	Compressed	▶ PL CN50 COB 2000 927 60D G3 IES 240726
Certificates	PDF	▶ CED - COIN COB DC G3 modules - 2025-08
Certificates	PDF	▶ PL ENEC 40031612 05082025
Eulumdat	Compressed	▶ PL-CN50-COB-2000-927-60D-G3 1 LDT 280726
CAD data	UNKNOWN	▶ PL-CN50-COB-2000-927-24D-G3 STEP
Mandatory Publications	PDF	▶ PL COIN COB G3 CE 4549560 090626
User instruction	PDF	▶ UI PL-CN35 50 111 COB G3

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
6937186151599 INVENTRONICS	PL-CN50-COB -2000- 927-60D-G3	Shipping carton box 20 Pieces	268 x 215 x 97 mm	5.59 dm ³	138.53 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit